Prima Latte AutoLuxe

QUICK START GUIDE

Each product is hand tested for quality reasons, so you may find traces of coffee grounds in the grinder

Breville

SCAN HERE
For your hands-on interactive guide.

1 WASH & FILL

Ensure unit is unplugged and remove red transit plug under the water tank. Wash the milk parts, aerators, hoppers, top burr and water tank in warm soapy water; dry thoroughly. Fit the charcoal filter in the basket in the water filter; fill the tank to MAX with cold water.



2 ADD YOUR BEANS

Once dry, lock the top burr and fit the hopper, aligning the centre grind-setting lines. Add coffee beans. Check internal brew mechanism, door and drip tray are fitted in place.

3 POWER ON & RINSE

Place cup under the coffee outlet. Press Power and let the automatic heat-up and rinse finish. Discard the rinse water.

4 RINSE THE MILK SYSTEM

Reassemble the milk tank. Half-fill the milk container with water and click assembled milk container into the steam outlet on the machine. Place cup under spout: select Milk, Large (3 bars), then Start/Stop. Discard the rinse water.



5 MAKE YOUR FIRST COFFEE

Place cup under outlet. Select your drink and press Start/Stop. For milk drinks, fill and fit the milk container first and click into place as per step 4; the milk based drink options will now become available.

MAKE IT YOUR WAY

Drink size
Press: small, medium or large.

Strength
Press to increase coffee strength.

Milk amount
Press to increase volume of milk.

My Way
Press: profiles 1-4. Hold 1 sec: save.

Read the safety instructions before use. For full setup, cleaning and care, scan the QR code.